

TRAP MOSQUITO LIGHT BATTERY POWERED TOC

JOHN W. HOCK COMPANY

MODEL #: 512.MIL

Manufacturer's PHONE: (352) 378-3209 FAX: (352) 372-1838

Website: <http://www.JohnWHock.com/products/512.htm>

AAC "J" ITEM NSN 3740-01-106-0091

UA's: 7124, 215B

**USAMMA POC: Customer Relations Management, 301-619-4301/4316, DSN 343-4301/4316
UNIT PRICE: \$253.38**

System Description: The CDC Miniature Light Trap Model 512.MIL was developed by the U.S. Centers for Disease Control to provide a reliable and portable sampling device for the collection of mosquitoes and sand flies used in arbovirus and taxonomic studies. This battery operated trap is being used throughout the world. It has become a standard, battery-operated survey tool for mosquito control operations. The 512.MIL trap comes complete with motor, fan, lamp, power cord, rain shield, terminals, battery holder (4 D-cell) and a double ring collection bag. The trap can be powered by 4 D-cell batteries or a rechargeable 6V gel cell battery w/ 10 amps or greater.

Feature:

- Use with collection bag or killing jar
- Downdraft fan keeps catch in the collection bag



**TRAP MOSQUITO LIGHT
MODEL # 512.MIL
NSN 3740-01-106-0091**

TRAP MOSQUITO LIGHT BATTERY POWERED PHYSICAL & ENVIRONMENTAL SPECIFICATIONS

Dimensions (shipping)	Height	15 inches
	Width	15 inches
	Depth	7 inches
Cube		0.9 cu ft
Weight		3.5 lb
Storage Temperature	-17° to 40° C	0° to 100° F
Operating Temperature	0° to 40° C	32° to 104° F
Power Requirements	Batteries should NOT be stored above 90°F	6 VDC provided by (4) D-cell batteries OR (1) 6V gel cell battery of 10 amps or more
	300 milliamps/hour required to operate	

TRAP MOSQUITO LIGHT BATTERY POWERED (START-UP)

NSN	NOTES	Nomenclature	PN	QTY	UI	Unit Price	Total Price	DIST/MFG	Shelf Life, months	Refrig Y/N
3740011060091		Trap mosquito light battery powered	512.MIL	1	EA	\$253.38	\$253.38	John W Hock	indef	N
7610015437003		Manual, operator		2	EA	Included w/ 0091 NSN	Included w/ 0091 NSN	John W Hock	indef	N
		Parts list w/ prices		1	EA	Included w/ 0091 NSN	Included w/ 0091 NSN	John W Hock	indef	N

**NOTE: [CLICK FOR USER MANUAL /
http://www.johnwhock.com/products/512.htm](http://www.johnwhock.com/products/512.htm)**

**NOTE: BATTERIES SHOULD NOT BE STORED ABOVE 90°F/32°C
BATTERIES SHOULD BE STORED FULLY CHARGED, PLACED ON
CHARGER ONCE EVERY 6 MONTHS. DO NOT FULLY DISCHARGE
BATTERY OR IT WILL NOT RE-CHARGE.**