

REFRIGERATOR MECHANICAL COMMERCIAL: BLOOD BANK TOC

HARRIS MFG CO INC

NOW MANUFACTURED BY THERMO FISHER SCIENTIFIC

MODEL #: HLT30V-4BB

Manufacturer's PHONE: (828) 658-2711 FAX: (828) 658-0363

Website: www.harrisphq.com/home.htm

AAC "W" ITEM NSN 4110-01-158-7992

ACC "J" ITEM NSN 4110-01-422-6809

UA's: 504A, F303, N304, N704

USAMMA POC: Customer Relations Management, 301-619-4301/4316, DSN 343-4301/4316

UNIT PRICE: \$8,749.00

System Description: Harris blood bank refrigerators are designed to maintain 39° F operating temperature with excellent temperature uniformity, fast recovery after door openings, and quick response to increased blood load.

Features:

- All models include standard high/low alarm, alarm and probe testing, and temperature monitoring and chart systems for permanent records
- Automatic defrost function, microprocessor controlled
- Adjustable temperature control, range 34° F to 46° F, factory pre-set to 39° F
- Set point security with key-operated triple-position master switch controls power to all systems for added safety
- Audible/visual warnings for door ajar, low alarm battery, system maintenance and power failure
- Alarm set points factory pre-set to warn of temperature deviation at 42° F or 35° F
- A graphic thermometer glows green for normal operation. Top bar flashes if temperature exceeds set point parameters, lower bulb flashes during under temperature condition
- Defrost sensor manages automatic defrost cycle, minimizes trace amounts of frost build-up, and maintains refrigeration coil efficiency for most economical, responsive performance
- Standard alarm silence, ring back and automatic reset functions
- Convenient push button alarm test with battery back-up to assure system readiness. Remote alarm contacts standard on all models



**REFRIGERATOR MECHANICAL
COMMERCIAL: BLOOD BANK
MODEL # HLT30V-4BB
NSN # 4110-01-422-6809**

**REFRIGERATOR MECHANICAL COMMERCIAL
PHYSICAL AND ENVIRONMENTAL SPECIFICATIONS**

Dimensions	Height	77.5 inches
	Width	28 inches
	Depth	36.2 inches
Cube		45.46 cu ft
Shipping Weight		505 lbs
Operating Temperature Range		65° F to 85° F
Relative Humidity (in use)		Less than 85%, non-condensing
Chart Recorder Paper Temperature Range		-175° F to 122° F
Power Requirements		115 VAC 60 Hz
Amps		9.4 amps
Watts		1,081 watts

REFRIGERATOR MECHANICAL COMMERCIAL (START-UP)

NSN	Notes	Nomenclature	PN	QTY	UI	Unit Price	Total Price	DIST/MFG	Shelf Life, months	Refrig Y/N	CONUS Ship Time, weeks
4110014226809	Included W/NSN	Refrigerator Mechanical Commercial: Blood Bank	HLT30V-4BB	1	EA	\$8,749.00	\$8,749.00	Thermo Electron	indef.	N	3
See Resupply		Chart recorder paper	90520H11	1	52/PG	Included W/0895 NSN	Included W/0895 NSN	Thermo Electron	N/A	N	3
7610015437003		Operators Manual	34830H28	1	EA	Included W/0895 NSN	Included W/0895 NSN	Thermo Electron	N/A	N	3
7610015436723	Not Included W/NSN	Service Manual	313398H02	1	EA	\$46.00	\$46.00	Thermo Electron	N/A	N	3