

**METER NOISE LEVEL 2.75 X 7.6 X 1.0 IN IMPULSE INTEGRATING SOUND
LEVEL TOC**

QUEST TECHNOLOGIES

MODEL #: 2200-10

Manufacturer's PHONE: (262) 567-9157 FAX: (262) 567-4047

Website: <http://www.Quest-Technologies.com>

AAC "L" ITEM NSN 6625-01-449-8480

UA's: 109A, 216B, 1109

**USAMMA POC: Customer Relations Management, 301-619-4301/4316, DSN 343-4301/4316
UNIT PRICE: \$1,477.73**

System Description: The db-2200 offers superior noise measurement and analysis. This Type 2 meter provides five operating modes and calibration is as simple as a press of a button. The large liquid crystal display provides up-to-the-second reading in 0.1 dB (decibel) increments as well as a low battery condition. The slide switches make the meters extremely easy to operate even while wearing gloves. The molded polymer case is lightweight and compact in size. Great portability makes the db-2200 the perfect choice for many applications. Includes WS-7 windscreen and QC-10 calibrator w/adapter.

Features:

- 30 to 140 dBA (decibels acoustic) measurement range
- Fast, slow, peak & impulse response modes
- "A", "C" and "Z" (linear) weighting modes
- Selectable 3 & 5 dB exchange rates
- Displays SPL (sound pressure level), LEQ (equivalent continuous noise level), run time, maximum SPL, minimum SPL & % overload
- Low battery indicator
- Simple one-button field calibration
- Tough, RFI (radio frequency interference)-shielded construction
- Approx. 25 hours operation per battery
- AC/DC output jack for recorders
- Certified intrinsically safe

**METER, NOISE LEVEL
MODEL # 2200-10
NSN 6625-01-449-8480**



**METER NOISE LEVEL
PHYSICAL & ENVIRONMENTAL SPECIFICATIONS**

Dimensions	Height	7 inches
	Width	2.8 inches
	Depth	1.3 inches
Cube		0.014 cu ft
Weight		10.3 ounces
Storage Temperature		-4° to 140° F
Operating Temperature		14° to 122° F
Power Requirements		9 VDC

**METER NOISE LEVEL
(START-UP)**

NSN	NOTES	Nomenclature	PN	QTY	UI	Unit Price	Total Price	DIST/MFG	Shelf Life, months	Refrig Y/N	CONUS Ship Time, weeks
6625014498480		Meter, noise level	2200-10	1	EA	\$1,477.73	\$1,477.73	Quest Technologies	indef	N	4
		Battery, nonrechargeable, 9V		1	EA	Included w/ 8480 NSN	Included w/ 8480 NSN	Quest Technologies	36	N	4
		Case, molded polymer	059-533	1	EA	Included w/ 8480 NSN	Included w/ 8480 NSN	Quest Technologies	indef	N	4
		Windscreen	WS-7	1	3/PG	Included w/ 8480 NSN	Included w/ 8480 NSN	Quest Technologies	indef	N	4
		Calibrator	QC-10	1	EA	Included w/ 8480 NSN	Included w/ 8480 NSN	Quest Technologies	indef	N	4
		Calibrator adapter	56-990	1	EA	Included w/ 8480 NSN	Included w/ 8480 NSN	Quest Technologies	indef	N	4
		Instructions		1	EA	Included w/ 8480 NSN	Included w/ 8480 NSN	Quest Technologies	indef	N	4

NOTE: [CLICK FOR INSTRUCTION MANUAL](#)