

INCUBATOR MINI-FIELD COLD ROLLED STEEL

MANUFACTURER: SCIMETRICS, INC.

Manufacturer Model# STDV

Manufacturer's PHONE: (281) 565-0066 FAX: (281) 565-0570

Manufacturer's Website: <<http://www.ScimetricsInc.com>>

AAC 'L' ITEM NSN 6640-01-466-9987

USAMMA POC: Customer Relationship Management 301-619-1288/4301 - DSN 343-1288/4301

UNIT PRICE: \$2,450.00

System Description: This item is a mini (1.2 cu ft interior) incubator made of stainless steel, used to culture or grow microorganisms in the field for proper identification by a microbiology technician.

Features:

- High portability
- Rugged – made of stainless steel
- Can switch between 120 VAC, 60 Hz and 220 VAC, 50 Hz using the two power cords provided
- 2 adjustable stainless shelves \pm 1 inch



INCUBATOR MINI-FIELD COLD ROLLED STEEL HIGH IMPACT - FRONT VIEW
PART # STDV
NSN 6640014669987



INCUBATOR MINI-FIELD COLD ROLLED STEEL HIGH IMPACT - REAR VIEW
PART # STDV
NSN 6640014669987



**BACKUP POWER SUPPLY SYSTEM
PART # 7098**



**INSULATED CARRYING CASE WITH WHEELS
PART # 7099
NSN 6640015583654**

**INCUBATOR MINI-FIELD COLD ROLLED STEEL
PHYSICAL & ENVIRONMENTAL SPECIFICATIONS**

Item Dimensions	Height (Inches)	15.6
	Width (Inches)	17.6
	Length (Inches)	23.5
	Cube (Cubic Feet)	3.7339
	Weight	61 lbs
Ship Dimensions	Height (Inches)	
	Width (Inches)	
	Length (Inches)	
	Cube (Cubic Feet)	
	Weight	
Storage Temp		Max of 158° F (70° C)
Operating Temp		From +7° F (+5° C) above ambient temperature to 140° F (60° C)
Storage Humidity		Can be close to 100%
Operating Humidity		
Amps		1.78 @ 120 VAC; 0.8 / @ 220 VAC
Watts		200
Power Requirements	24 VDC (with optional voltage inverter); 120 VAC, 60 Hz or 220 VAC, 50 Hz	
Notes	Interior Humidity: Up to 98% (adjusted by water pan size)	

**INCUBATOR MINI-FIELD COLD ROLLED STEEL
ACCESSORIES & CONSUMABLES - STARTUP**

NSN	Notes	Nomenclature	MFR PN Scimetrix, Inc.	DIST PN	QTY	UI	Unit Price	Total Price	Shelf Life Mon.
6640014669987		Incubator Mini-Field Cold Rolled Steel	STDV		1	EA	\$2,450.00	\$2,450.00	N/A
	no NSN required	Manual, Operator	STDV- Manual		1	EA	Incl w/NSN 9987	Incl w/NSN 9987	N/A
6640015574334		Power Cord 120V 60Hz	STDV-120		1	EA	Incl w/NSN 9987	Incl w/NSN 9987	N/A
6640015574342		Power Cord 220V 50Hz	STDV-240		1	EA	Incl w/NSN 9987	Incl w/NSN 9987	N/A
6640015583972		Stainless Shelf	STDV- 315-6		2	EA	Incl w/NSN 9987	Incl w/NSN 9987	N/A